



Pneumatic Wheels - Plastic Rims

- **For loads up to 370kg per wheel.**
- Complete non rust wheels with wide flotation tyre options.
- Ideal for irrigation equipment, lightweight beach or watercraft trailers, heavy duty barrows etc.



PW200-N25
-300 x 8



PW200-B25
-480/400 x 8



PWW200-N25
-480/400 x 8



PWW200-N25
-16/650 x 8



PWY200-N25
-16/650 x 8

CODE	Rim							
	(mm)	(mm)	(mm)		(mm)	(mm)	KG	
8"	PW200-N25 - 300 x 8 (2 ply)	200	72	25.4	Bush	75	365	110kg
	PW200-N25 - 350 x 8 (4 ply)	200	72	25.4	Bush	91	391	150kg
	PW200-N25 - 480/400 x 8 (2 ply)	200	72	25.4	Bush	105	400	198kg
*Nylon bush options N - 19.05, 25.4mm *Ball bearing options B - 19.05, 25.4mm								
8"	PWW200-N25 - 480/400 x 8 (2 ply)	200	80	25.4	Bush	115	400	198kg
	PWW200-N25 - 16/650 x 8 (4 ply)	200	80	25.4	Bush	164	406	282kg
*Nylon bush options N - 19.05, 25.4mm *Ball bearing options B - 19.05, 25.4mm								
8"	PWY200-N25 - 16/650 x 8 (4 ply)	200	101	25.4	Bush	164	406	282kg
	PWY200-N25 - 18/850 x 8 (4 ply)	200	101	25.4	Bush	216	460	370kg
*Nylon bush options N - 19.05, 25.4mm *Ball bearing options B - 19.05, 25.4mm								

NB When ordering, state bush or bearing size. eg. PW200-B25 - 300x8 (25.4mm bearing)
For rims only, see page 52