



Twin Wheel Castors

- For loads up to 50kg per castor.
- Highly manoeuvrable.
- Economical.
- Attractive.
- Large range of fittings for timber and metal.
- All 40mm and 50mm castors available with brake.



TW40-TH



TW50-P



TW50-P-B



TW50-S

(for socket option see page 108)



TW50-EF-19R

(for expanding fitting options see page 9)



TW50-M8







TW50-C11

(office chair model)



TW50-U18

CODE	 (mm)		 KG	 (mm)	Plate/Fitting Type
TW30-P	30	Nylon	30kg	46	30 x 30mm Plate
TW30-S	30	Nylon	30kg	46	Stem & Socket
TW30-M6	30	Nylon	30kg	46	M6 x 15mm Thread
TW40-P	40	Nylon	40kg	55	38 x 38mm Plate
TW40-S	40	Nylon	40kg	55	Stem & Socket
TW40-TH	40	Nylon	40kg	55	30 x 12.5mm Top Hat
TW40-516	40	Nylon	40kg	55	5/16" x 19mm BSW Thread
TW40-M8	40	Nylon	40kg	55	M8x 20mm Thread
NB. For braked castor, add 'B' after code.					
TW50-P	50	Nylon	40kg	65	38 x 38mm Plate
TW50-C8	50	Nylon	40kg	55	Stem & Circlip 8mm
TW50-C11	50	Nylon	40kg	65	Stem & Circlip 11mm
TW50-38	50	Nylon	40kg	65	3/8" x 19mm UNF Thread
TW50-516	50	Nylon	40kg	65	5/16" x 19mm BSW Thread
TW50-M8	50	Nylon	40kg	65	M8x 15mm Thread
TW50-M10	50	Nylon	40kg	65	M10 x 15mm Thread
TW50-EF	50	Nylon	40kg	55	M10 Thread for expanding fitting
TW50-S	50	Nylon	40kg	65	Stem 8mm
TW50-U16	50	Nylon	40kg	65	16mm U-Bracket
TW50-U18	50	Nylon	40kg	65	18mm U-Bracket
TW50-U25	50	Nylon	40kg	65	25mm U-Bracket
NB. For braked castor, add 'B' after code.					
TW60-P	60	Nylon	50kg	80	38 x 38mm Plate
TW60-C11	60	Nylon	50kg	80	Stem & Circlip 11mm